

Europäisches Patentamt

European Patent Office

Office européen des brevets



EP 0 778 478 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3: 24.09.1997 Bulletin 1997/39

(51) Int. Cl.⁶: **G02B 6/293**, G02B 6/12

(43) Date of publication A2: 11.06.1997 Bulletin 1997/24

(21) Application number: 96119367.9

(22) Date of filing: 03.12.1996

(84) Designated Contracting States: DE FR GB

(30) Priority: 04.12.1995 JP 315385/95

(71) Applicant: NEC CORPORATION Tokyo (JP)

(72) Inventors:

 Kurata, Kazuhiko Minato-ku, Tokyo (JP)


(11)

- Kimura, Naoki Minato-ku, Tokyo (JP)
- (74) Representative: VOSSIUS & PARTNER Siebertstrasse 4 81675 München (DE)

(54) Waveguide type wavelength multiplexing/demultiplexing module

(57)In a waveguide type wavelength multiplexing/demultiplexing (WDM) module, a wavelength multiplexing/demultiplexing function can be realized with a half length of the conventional directional coupling device. The waveguide type WDM module is comprised of: a common waveguide for conducting first signal light having a first wavelength and second signal light having a second wavelength; common light input/output means coupled to the common waveguide; a substrate containing a WDM unit for multiplexing/demultiplexing the first signal light and the second signal light; a first waveguide for conducting the first signal light; first light input/output means optically coupled to the first waveguide; and second light input/output means for inputting/outputting the second signal light. The WDM unit includes a directional coupling type WDM device constituted by two sets of waveguides connected to the first waveguide and the common waveguide respectively. The directional coupling type WDM device is comprised of: a first edge surface perpendicular to a waveguide for constituting a directional coupling unit at a position equal to a half of a complete coupling length with respect to the first signal light in the directional coupling unit; and wavelength selecting means arranged at the first edge surface, for reflecting the first signal light and for passing therethrough the second signal light; and the second light input/output means is comprised of coupling means for optically being coupled to the second signal light at the first edge surface.

Fig. 2





EUROPEAN SEARCH REPORT

Application Number EP 96 11 9367

	Citation of document with it	DERED TO BE RELEV indication, where appropriate,	Relevant	CLASSIFICATION OF THE
Category	Citation of document with it of relevant pa		to claim	APPLICATION (Int.CL6)
Х	PATENT ABSTRACTS OF JAPAN vol. 095, no. 010, 30 November 1995 L JP 07 168038 A (NEC CORP), 4 July 1995,		1,2,7,8	G02B6/293 G02B6/12
A	* abstract *	A (NEC CORF), 4 outy 1995,		
A	WO 95 12136 A (UNIV RUTGERS) 4 May 1995 * page 23, line 24 - page 24, line 16 * * figure 8 *		1,9,13	
A	ELECTRONICS LETTERS vol. 31, no. 2, 19 page 132/133 XP0005	January 1995, 04805	1,9,13	**************************************
		LOCAL ACCESS NETWORKS"		\$°
Α .	DE 44 04 756 A (SIE * page 3, line 21 - * figure 1 *	995 1,9,13		
A,D	OPTICAL FIBER COMMU	NICATION. SUMMARIES THE CONFERENCE OFC	OF 1,9,13	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
	'95, SAN DIEGO, FEB. 26 - MAR. 3, 1995, vol. 8, 26 February 1995, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 370-373, XP000618290 YAMADA Y ET AL: "A HYBRID INTEGRATED OPTICAL WDM TRANSMITTER/RECEIVER MODULE FOR OPTICAL SUBSCRIBER SYSTEMS UTILIZING A PLANAR LIGHTWAVE CIRCUIT PLATFORM" * whole document *		-	G02B
			G A	
	. *			
	e)(·		
	The present search report has b	een drawn up for all claims		
	Place of search	Date of completion of the sear	4	Examiner
	BERLIN	22 July 1997	Lu	ck, W
Y : pai doc	CATEGORY OF CITED DOCUME ricularly relevant if taken alone ricularly relevant if combined with an tument of the same category thological background	E : earlier pat after the f other D : document L : document	principle underlying the cent document, but puriling date cited in the application cited for other reason	blished on, or on s